



BAC CABLE TIES

1.8.5

The BAC range of self locking cable ties offers a wide range of sizes for all applications and are precision moulded from Nylon 66 to meet the most stringent quality requirements.

Operating Temperature:..... -55°C to + 100°C
Specification: MIL23190D
UL Approved Flammability: UL94V class 2

Also available is the BAC Cable Tie Installation Tool for fast, safe tensioning and cut-off of cable ties. Features sturdy lightweight (320gms) aluminium body, with profiled plastic grip for maximum operator speed and comfort, and also incorporates a cable tie tail ejector. Adjustable for ties up to 4.8mm wide.

CABLE TIES

Length mm	Width mm	Maximum Bundle Diameter mm	Minimum Tensile Strength kp
80	2.4	15	8.0
100	2.5	18	8.1
160	2.5	40	8.1
200	2.5	50	8.1
140	3.6	35	18.2
200	3.6	50	18.2
295	3.6	76	18.2
160	4.8	40	22.2
196	4.8	47	22.2
304	4.8	76	22.2
370	4.8	102	22.2
200	7.6	50	54.4
292	7.6	76	54.4
368	7.6	102	54.4
430	9.0	110	79.4
536	9.0	140	79.4
710	9.0	190	79.4
812	9.0	240	79.4